
SH-0264MG+




Line	ORIGINAL LINE
Application	CAR | HELI | AIRPLANE
Servo Size	Micro
Operating Voltage	4.8V-6.0V
Speed	0.06 s/60°
Torque	1.2 kg/cm | 16.7 oz/in
Amplifier Type	Digital Controller
Motor Type	DC Motor
Case Type	Hybrid (Aluminium/Composite)
Protection	Dust Resistant
Dimensions (L x W x H)	22.8 x 12 x 25.4 mm
Weight	15 g
Gear Type	Heavy-Duty Metal

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Normal	**Potentiometer**	VR
Speed @4.8V	0.08 s/60°	**Cable**	26 AWG 250 ±5 mm
Torque @4.8V	0.8 kg/cm | 11.1 oz/in	**Connector**	JR Connector
Speed @6.0V	0.06 s/60°	**Stall Current @4.8V**	1200 mA
Torque @6.0V	1.2 kg/cm | 16.7 oz/in	**Operating Current @4.8V**	150 mA
PCB Board	10-bit	**Stall Current @6.0V**	1400 mA
Rotating Direction	Clockwise (when 1000→2000 µsec)	**Operating Current @6.0V**	180 mA
Max Travel	~130° (when 800→2200 µsec)	**Idle Current**	5 mA
Operating Travel	90° (when 1000→2000 µsec)	**Dead Band Width**	3-5 µsec
Neutral Position	1500 µsec	**Frequency Range**	50-360 Hz
Horn Gear Spline	21T(Φ4.8)	**Control System**	Pulse width modification
Bearing	2x Ball Bearings	**Operating Temperature**	-10°C to 50°C