
SAVÖX

SV-0320+




Line	HOBBY LINE
Application	CAR | AIRPLANE
Servo Size	Standard
Operating Voltage	6.0V-7.4V
Speed	0.13 s/60°
Torque	6 kg/cm | 83.3 oz/in
Amplifier Type	Digital Controller
Motor Type	DC Motor
Case Type	Composite
Protection	Water Resistant
Dimensions (L x W x H)	40.75 x 20 x 38 mm
Weight	46 g
Gear Type	High-Strength Composite

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	**Potentiometer**	VR
Speed @6.0V	0.16 s/60°	**Cable**	26 AWG 300 ±5 mm
Torque @6.0V	4.5 kg/cm | 62.5 oz/in	**Connector**	JR Connector
Speed @7.4V	0.13 s/60°	**Stall Current @6.0V**	1300 mA
Torque @7.4V	6 kg/cm | 83.3 oz/in	**Operating Current @6.0V**	180 mA
PCB Board	12-bit	**Stall Current @7.4V**	1600 mA
Rotating Direction	Counterclockwise (when 1000→2000 µsec)	**Operating Current @7.4V**	240 mA
Max Travel	~164° (when 800→2200 µsec)	**Idle Current**	5 mA
Operating Travel	120° (when 1000→2000 µsec)	**Dead Band Width**	3-5 µsec
Neutral Position	1500 µsec	**Frequency Range**	50-360 Hz
Horn Gear Spline	25T(Φ6)	**Control System**	Pulse width modification
Bearing	1x Ball Bearing	**Operating Temperature**	-10°C to 50°C