
SAVÖX

SW-0241MG+




Line	BLUE LINE
Application	CAR | BOAT
Servo Size	Large
Operating Voltage	6.0V-7.4V
Speed	0.17 s/60°
Torque	40 kg/cm | 555.5 oz/in
Amplifier Type	Digital Controller
Motor Type	DC Motor
Case Type	Hybrid (Aluminium/Composite)
Protection	Waterproof (IP67)
Dimensions (L x W x H)	65.8 x 30 x 61.6 mm
Weight	200 g
Gear Type	Heavy-Duty Metal

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	**Potentiometer**	VR
Speed @6.0V	0.21 s/60°	**Cable**	22 AWG 200 ±5 mm
Torque @6.0V	30 kg/cm | 416.6 oz/in	**Connector**	JR Connector
Speed @7.4V	0.17 s/60°	**Stall Current @6.0V**	4600 mA
Torque @7.4V	40 kg/cm | 555.5 oz/in	**Operating Current @6.0V**	150 mA
PCB Board	10-bit	**Stall Current @7.4V**	5700 mA
Rotating Direction	Counterclockwise (when 1000→2000 µsec)	**Operating Current @7.4V**	180 mA
Max Travel	~130° (when 800→2200 µsec)	**Idle Current**	5 mA
Operating Travel	100° (when 1000→2000 µsec)	**Dead Band Width**	3-5 µsec
Neutral Position	1500 µsec	**Frequency Range**	50-360 Hz
Horn Gear Spline	15T(Φ7.8)	**Control System**	Pulse width modification
Bearing	2x Ball Bearings	**Operating Temperature**	-10°C to 50°C